

1.75 VPC

DISCHARGE RATINGS IN AMPS @ 77°F (25°C)

Battery Model	1'	15'	30'	1 h	2 h	3 h	4 h	5 h	6 h	8 h	10 h	12 h
8 OGi 200	599	345	234	146	87.3	63.9	49.1	41.3	35.9	28.4	23.3	19.8
10 OGi 250	702	422	289	181	108	79.2	60.8	51.1	44.3	35.1	28.8	24.4
12 OGi 300	803	496	344	216	129	94.5	72.5	60.9	52.8	41.7	34.3	29.1
14 OGi 350	903	575	397	250	150	109	83.8	70.4	61.0	48.1	39.5	33.5
16 OGi 400	1035	651	454	286	171	125	96.0	80.6	69.8	55.2	45.3	38.4
18 OGi 450	1131	723	507	321	192	140	107.6	90.4	78.3	61.9	50.7	43.0
5 OGi 400	530	430	333	230	145	108	87.7	74.1	64.6	51.9	43.7	37.6
6 OGi 480	614	506	395	275	173	130	105	89	77.5	62.3	52.5	45.2
7 OGi 560	697	582	456	319	202	152	122	103	90.4	72.7	61.2	52.7
8 OGi 640	773	654	517	364	231	173	140	118	103	83.0	69.9	60.2
9 OGi 720	848	720	567	397	249	186	150	126	109	87.7	73.7	63.2
10 OGi 800	1162	900	684	465	291	218	175	148	129	103	87.5	75.3
11 OGi 880	1142	933	724	501	315	235	189	160	139	112	94.4	81.1
12 OGi 960	1335	1047	796	539	334	248	198	167	145	116	97.5	83.7
13 OGi 1040	1359	1109	862	597	377	282	228	192	168	135	113	97.9
14 OGi 1120	1500	1207	929	637	399	298	240	202	176	141	118	102
15 OGi 1200	1524	1249	968	666	416	309	248	209	181	145	121	104
16 OGi 1280	1659	1359	1057	733	462	346	279	236	205	165	139	119
17 OGi 1360	1683	1402	1097	764	480	359	289	244	212	170	143	123
18 OGi 1440	1811	1491	1159	799	499	371	298	251	218	174	146	125
19 OGi 1520	2090	1665	1278	876	550	411	331	280	244	196	165	142
20 OGi 1600	2173	1742	1340	920	578	433	348	294	256	206	173	149
21 OGi 1680	2259	1819	1402	965	606	454	365	309	269	216	182	156
22 OGi 1760	2338	1888	1455	999	626	468	376	317	276	221	186	160
23 OGi 1840	2421	1956	1506	1030	642	479	384	323	281	224	188	162
24 OGi 1920	2499	2023	1557	1064	661	491	393	331	287	229	192	165
25 OGi 2000	2580	2116	1646	1141	719	538	434	367	319	256	216	185
26 OGi 2080	2655	2188	1706	1185	747	560	451	381	332	266	224	193
27 OGi 2160	2734	2262	1763	1225	772	578	465	393	342	274	231	198
28 OGi 2240	2808	2328	1813	1257	789	589	474	400	348	278	234	201
29 OGi 2320	2884	2396	1864	1290	807	602	483	407	354	283	237	204
30 OGi 2400	2956	2461	1912	1321	824	613	491	413	359	286	240	206

1.81 VPC

DISCHARGE RATINGS IN AMPS @ 77°F (25°C)

Battery Model	1'	15'	30'	1 h	2 h	3 h	4 h	5 h	6 h	8 h	10 h	12 h
8 OGi 200	442	293	208	136	83.7	62.0	48.0	40.5	35.2	27.9	23.0	19.5
10 OGi 250	518	357	256	168	103	76.7	59.3	50.1	43.5	34.4	28.4	24.1
12 OGi 300	582	417	303	200	123	91.4	70.6	59.6	51.8	41.0	33.7	28.7
14 OGi 350	648	477	348	231	142	105	81.6	68.8	59.8	47.3	38.8	33.0
16 OGi 400	745	545	398	264	163	120	93.2	78.6	68.3	54.1	44.5	37.8
18 OGi 450	807	604	443	296	182	135	103.7	88.1	76.6	60.6	49.9	42.3
5 OGi 400	391	350	282	205	135	103	84.2	71.7	62.7	50.7	42.8	36.9
6 OGi 480	454	412	334	244	162	123	101	86.0	75.2	60.8	51.4	44.2
7 OGi 560	515	472	385	283	188	144	117	100	87.7	70.9	59.9	51.6
8 OGi 640	572	530	434	321	215	164	134	114	100	81.0	68.5	58.9
9 OGi 720	628	583	476	350	232	176	143	121	106	85.5	72.0	61.9
10 OGi 800	858	740	585	418	273	207	169	143	125	101	85.8	73.9
11 OGi 880	844	759	612	446	294	223	182	155	135	109	92.4	79.5
12 OGi 960	986	857	678	484	313	236	191	162	141	113	95.7	82.1
13 OGi 1040	1004	904	729	532	352	268	219	186	163	131	111	95.9
14 OGi 1120	1109	984	788	569	374	283	230	196	171	138	116	100
15 OGi 1200	1127	1016	818	593	388	293	238	202	176	141	119	102
16 OGi 1280	1226	1107	894	652	432	328	268	228	199	161	136	117
17 OGi 1360	1245	1138	924	677	448	340	277	235	206	166	140	120
18 OGi 1440	1339	1212	978	710	466	352	286	242	211	170	143	123
19 OGi 1520	1544	1361	1087	784	515	391	319	271	237	191	161	139
20 OGi 1600	1606	1422	1138	823	542	411	335	285	249	201	170	146
21 OGi 1680	1669	1484	1190	862	568	431	351	299	261	211	178	153
22 OGi 1760	1728	1539	1234	893	586	444	361	307	268	216	182	157
23 OGi 1840	1789	1593	1276	920	602	454	369	313	273	219	185	158
24 OGi 1920	1847	1647	1319	950	619	467	378	320	279	224	189	162
25 OGi 2000	1907	1723	1392	1015	672	511	417	354	310	250	211	182
26 OGi 2080	1963	1780	1441	1053	698	531	433	368	322	260	219	189
27 OGi 2160	2022	1838	1488	1088	721	548	447	380	332	268	226	194
28 OGi 2240	2076	1889	1529	1116	737	559	455	386	337	272	229	197
29 OGi 2320	2133	1941	1571	1145	754	571	464	394	343	276	232	200
30 OGi 2400	2186	1991	1611	1172	770	581	472	400	349	280	235	202