

1.75 VPC

DISCHARGE RATINGS IN AMPS @ 77°F (25°C)

Battery Model	1'	15'	30'	1 h	2 h	3 h	4 h	5 h	8 h	10 h	12 h
12V 1 OGiV 25-N7	87.0	47.0	31.0	19.0	10.9	7.8	6.1	5.0	3.3	2.7	2.3
12V 2 OGiV 50-N7	174.0	95.0	62.0	37.0	21.9	15.5	12.1	10.0	6.6	5.4	4.6
12V 3 OGiV 75-N7	261.0	142.0	92.0	56.0	32.8	23.3	18.2	14.9	9.9	8.1	6.9
12V 4 OGiV 100-N7	349.0	190.0	123.0	75.0	43.8	31.0	24.2	19.9	13.1	10.7	9.1
12V 5 OGiV 125-N7	421.0	234.0	153.0	93.0	54.7	38.8	30.3	24.9	16.4	13.4	11.4
12V 6 OGiV 150-N7	495.0	280.0	183.0	111.0	65.7	46.6	36.4	29.9	19.7	16.1	13.7
6V 7 OGiV 175-N7	569.0	323.0	213.0	128.0	76.6	54.4	42.4	34.9	23.0	18.8	15.9
6V 8 OGiV 200-N7	641.0	369.0	244.0	146.0	87.6	62.1	48.5	39.9	26.3	21.5	18.2
6V 9 OGiV 225-N7	678.0	397.0	267.0	164.0	98.5	69.9	54.6	44.9	29.6	24.2	20.5
6V 10 OGiV 250-N7	715.0	421.0	289.0	183.0	109.0	77.7	60.6	49.9	32.9	26.9	22.8
6V 11 OGiV 275-N7	752.0	446.0	312.0	202.0	120.0	85.5	66.7	54.9	36.2	29.6	25.1
6V 12 OGiV 300-N7	789.0	472.0	333.0	220.0	131.0	93.2	72.8	59.9	39.5	32.3	27.4



1.81 VPC

DISCHARGE RATINGS IN AMPS @ 77°F (25°C)

Battery Model	1'	15'	30'	1 h	2 h	3 h	4 h	5 h	8 h	10 h	12 h
12V 1 OGiV 25-N7	61.0	42.0	29.0	18.0	10.8	7.7	6.0	5.0	3.3	2.7	2.3
12V 2 OGiV 50-N7	122.0	84.0	57.0	35.0	21.5	15.4	12.0	10.0	6.6	5.4	4.6
12V 3 OGiV 75-N7	184.0	125.0	85.0	53.0	32.3	23.1	18.1	14.9	9.9	8.1	6.9
12V 4 OGiV 100-N7	245.0	167.0	114.0	71.0	43.0	30.8	24.1	19.9	13.1	10.7	9.1
12V 5 OGiV 125-N7	293.0	202.0	140.0	89.0	53.8	38.4	30.1	24.8	16.4	13.4	11.4
12V 6 OGiV 150-N7	341.0	239.0	167.0	107.0	64.5	46.1	36.1	29.8	19.7	16.1	13.7
6V 7 OGiV 175-N7	389.0	274.0	194.0	124.0	75.1	53.7	42.1	34.7	23.0	18.8	15.9
6V 8 OGiV 200-N7	435.0	311.0	221.0	141.0	85.7	61.4	48.1	39.7	26.3	21.5	18.2
6V 9 OGiV 225-N7	472.0	341.0	244.0	157.0	96.3	69.0	54.1	44.6	29.5	24.2	20.5
6V 10 OGiV 250-N7	509.0	370.0	265.0	172.0	106.0	76.6	60.1	49.6	32.8	26.9	22.8
6V 11 OGiV 275-N7	544.0	399.0	287.0	188.0	117.0	84.2	66.1	54.5	36.1	29.6	25.1
6V 12 OGiV 300-N7	586.0	429.0	308.0	204.0	128.0	91.9	72.0	59.5	39.4	32.3	27.4

